

BUILT STRONG

SMARTRISE CUSTOM CABLING

Smartrise offers three custom-labeled traveler cables, and a 21-conductor custom-labeled hoistway cable. Each individual wire is labeled to correspond with din rails and terminals. This option minimizes wiring mistakes and speeds up overall installation. Non-custom traveler cables are available.

TRAVELER CABLE CONSTRUCTION

- Cabling core with Jute fillers in the interstices
- Nylon Binder with an open spiral wrap
- 95% Textile Braid Coverage
- 0.090" Jacket. Nominal Wall Black PVC

TRAVELER CABLE TECH SPECS

- Composite Conductor
- Textile Braid
- PVC Jacket

HOISTWAY CABLE CONSTRUCTION

- One insulated Core Conductor
- Dual layers of insulated conductors
- Nylon Binder with an open spiral wrap

HOISTWAY CABLE TECH SPECS

- Temperature 60C
- Voltage 300 V

| | TRAVELER CABLE #1 | TRAVELER CABLE #2 | TRAVELER CABLE #3 | TRAVELER CABLE #4 | TRAVELER CABLE #5 | HOISTWAY CABLE |
|----------------------------|---|-------------------|-------------------|-------------------|-------------------|---------------------------------|
| CUSTOM LABELING | Yes | Yes | Yes | No | No | Yes |
| # OF CONDUCTORS | 26 | 33 | 43 | 27 | 69 | 21 |
| CORE | Jute | Steel | Steel | Jute | Steel | N/A |
| DIAMETER | 1.04" | 1.19" | 1.37" | .94" | 1.57" | .64" |
| # OF 14 AWG | 4 | 4 | 4 | 3 | 5 | 0 |
| # OF 18 AWG | 14 | 20 | 23 | 20 | 40 | 21 |
| # OF 20 AWG SHIELD. | 4 | 4 | 7 | 2 | 11 | 0 |
| COAXIAL (RG/6U) | 0 | 1 | 2 | 0 | 2 | 0 |
| APPROVALS | UL Type ETT, NEC Compliant, CSA Type ETT, CSA FT1 | | | | | UL & CSA Hoistway NEC Compliant |

All Smartrise Traveler Cables come with Kellems® Grips

