

V2

ELEVATOR CONTROL SYSTEM

AC TRACTION CONTROLLER

Performs serial data exchanges between the machine room, top of the car, and car operating panel. This simplifies programming, cabling, and parts. Extensive communication and operator interfaces (LCD Display) are built into our standard controller.



APPLICATION	Supports geared, gearless, overhead, basement, and machine room-less
FEEDBACK	Distance and velocity
DISPATCH	Up to 8 car group
MAX OPENINGS	64
MAX SPEED	800FPM
DIMENSIONS	L - 39"H x 30"W x 14"D XL - 48"H x 36"W x 16"D
CABINET	NEMA 1, 4, 4x, and 7
POWER REGEN	Dynamic Braking Resistors

Optional Accessories

- Local and Remote Monitoring
- SmartConnect Pre-wired Inspection Box
- Power Back Regenerative Kit
- Harmonic Filter
- Isolation Transformer
- Load-Weighing Device
- AC Motor
- Emergency Rescue Device
- Voice Annunciator Interface
- Card Reader Access
- Traveler and Hoistway Cables
- OSHPD Certified
- Air Conditioning Unit

Contact our Sales Department at sales@smartrise.us to order or for more information.



Phone: 469-678-8000

Address: 1235 N. Union Bower Rd
Irving, TX 75061

Website: SMARTRISE.US